

BEAUTIFUL INNOVATIONS FOR YOUR KITCHEN

Catalogue 2017



falmec

**BEAUTIFUL
INNOVATIONS FOR
YOUR KITCHEN**

Catalogue 2017/18

falmec



ALPHABETIC INDEX

A

- 65 Afrodite
- 64 Artemide

D / E

- 70 Danilo
- 50 Down Draft
- 71 Eros

F / G

- 40 Flipper
- 21 Gr. Incasso NRS®

L

- 16 Line Pro NRS®
- 42 Lumen
- 44 Lumen Isola 175
- 18 Lumina NRS®
- 54 Lux

M

- 69 Mara
- 26 Massimo Pro
- 17 Massimo Pro NRS®
- 62 Mercurio
- 57 Mira Top
- 46 Move

N / O

- 36 Nube
- 35 Nuvola 140
- 34 Nuvola 90

P

- 20 Plane NRS®
- 56 Plane Top
- 32 Polar
- 33 Prestige
- 30 Prisma
- 25 Pyramid Pro
- 15 Pyramid Pro NRS®

Q / R

- 38 Quasar
- 58 Rialto Top

S

- 66 Sabina
- 68 Built-in Mercurio
- 37 Stella

V

- 67 Valentina
- 48 Virgola
- 63 Vulcano

Z

- 2421 Zeus Pro
- Zeus Pro NRS®

INSTALLATION INDEX

WALL

- 65 Afrodite
- 64 Artemide
- 40 Flipper
- 16 Line Pro NRS®
- 42 Lumen
- 18 Lumina NRS®
- 54 Lux
- 62 Mercurio
- 57 Mira Top
- 20 Plane NRS®
- 56 Plane Top
- 32 Polar
- 33 Prestige
- 30 Prisma
- 25 Pyramid Pro
- 15 Pyramid Pro NRS®
- 38 Quasar
- 58 Rialto Top
- 63 Vulcano
- 24 Zeus Pro
- 14 Zeus Pro NRS®

ISLAND

- 42 Lumen
- 44 Lumen Island 175
- 18 Lumina NRS®
- 54 Lux
- 62 Mercurio
- 57 Mira Top
- 20 Plane NRS®
- 56 Plane Top
- 32 Polar
- 33 Prestige
- 25 Pyramid Pro

BUILT-IN

- 70 Danilo
- 71 Eros
- 21 Gr. Incasso NRS®
- 69 Mara
- 26 Massimo Pro
- 17 Massimo Pro NRS®
- 46 Move
- 66 Sabina
- 68 Built-in Mercurio
- 67 Valentina
- 48 Virgola

CEILING

- 36 Nube
- 35 Nuvola 140
- 34 Nuvola 90
- 37 Stella

SILENCE - NRS®



21 Gr. Incasso NRS®



16 Line Pro NRS®



18 Lumina NRS®



17 Massimo Pro NRS®



20 Plane NRS®



15 Pyramid Pro NRS®



14 Zeus Pro NRS®

PROFESSIONAL



26 Massimo Pro



25 Pyramid Pro



24 Zeus Pro

DESIGN



50 Down Draft



40 Flipper



42 Lumen



44 Lumen Isola 175



46 Move



36 Nube



34/35 Nuvola



32 Polar



33 Prestige



30 Prisma



38 Quasar




37 Stella



48 Virgola

FASTEEL



54 Lux



57 Mira Top



56 Plane Top



58 Rialto Top

POTENZA



65 Afrodite



64 Artemide



70 Danilo



71 Eros



69 Mara



62 Mercurio



66 Sabina



68 Built-in Mercurio



67 Valentina



63 Vulcano

The company.

Founded in 1981, Falmec has evolved from a small manufacturing company to a leading force both in the national and international market, gaining extensive experience in the design and production of ventilation hoods. Cutting-edge research, flexibility in production, development of new technologies and original creativity endow the Falmec collections with strong added value in terms of innovation, and a totally unique blend of design and cutting edge technology, reaching the highest levels of Italian excellence in the world.

Made in Italy.

From initial design to finished product, all of Falmec's creations are achieved through a multi-step process that is run entirely onsite at the company headquarters, located near Venice. Our products offer an absolute guarantee of quality in design, materials and construction, staying true to the best in Italian manufacturing tradition.

Quality.

Each Falmec product is the result of careful research, meticulous testing and extreme precision in their construction. Falmec's facilities rely on state of the art technology and are equipped with numerous robotic lines that enable us to meet top quality standards. From steel laser cutting to automated contouring, from welding to coating, to the final assembly of the motors and electronics, each operating phase is carried out with the utmost attention. All in keeping with the requirements set by the strictest international quality standards.







Technology and Design.

Innovation. Performance.
Energy efficiency.
Ease of installation. Design.
These are the key concepts
of all Falmec projects.
They are the outcome of
ongoing research that
considers aesthetic, material
and technology as a single
set in order to achieve the
perfect synergy.
Falmec's products satisfy
every sense: smell, for
the effectiveness of air
movement; sight and touch,
thanks to refined design
and quality of material;
sound, for extremely silent
performance.

Select steel.

Falmec selects and uses
AISI 304 stainless steel,
with an alloy containing 18%
chromium and 8% nickel.
Hygienic, easy to clean, highly
resistant to corrosion.
AISI 304 is by far the best
material for the production of
cooker hoods superior in both
domestic and professional
kitchens.





SILENCE NRS®

Finally a hood that is extremely quiet.

With our innovative NRS® technology, Falmec has created a product that combines superior performance and super quiet operation. Significant effort has gone in to making this product one of the quietest hoods in the market.



**The difference is not felt,
but experienced.**

A system developed by Falmec in collaboration with laboratories specialised in the study of fluid dynamics, NRS® (Noise Reduction System) has enabled us to create a collection of incredibly quiet ventilation hoods that effectively enhance the quality of life in the kitchen. NRS® technology allows you to cook, work, talk and listen to music without hearing the noise typical of ventilation hoods, while benefiting from the best air suction performance.

**Up to -86%
less noise.**

Thanks to the study of air flow and to the materials used, NRS® ventilation hoods reduce noise to a whisper-like quiet level. The NRS® system guarantees extraction of cooking fumes, and NRS® hoods also provide superior sound performance when using a recirculation filter, or our long lasting regenerating carbon filter.


Compared to today's standard hoods, the noise level has been reduced dramatically. The benefit in the kitchen is extraordinary. The 'perception' of noise follows a logarithmic scale: each decrease of 1dB corresponds to a reduction in the perceived noise level of about 20%. In other words, for every decrease of 3db perceived noise is halved.



collection
silence

**Better quality of life,
without noise disturbance**

The dynamics of the airflow being drawn through the hood was studied using innovative computer software; this allowed Falmec to develop the products so that airflow is optimised, eliminating any resistance, the principal cause of noise in extraction. Falmec invested time and resources in the development of new materials that would be best suited to this particular application because of their sound absorbing qualities. These materials have been designed to contain any noise produced by the movement of air, further increasing the reductions in noise already achieved by the optimisation of airflow.



Schematics of a NRS Hood airflow. The soundproofing of the motor chamber and the optimization of the airflow path reduce operating noise to a minimum.


Tangential motor 500 CFM

Data relates to Plane NRS® 36"

Motor speed	1	2	3	4
Noise I.E.C.60704-2-13 dB (A) re 1pW	37	41	45	53
Capacity CFM - I.E.C.615991 normalized piping	160	225	290	420
Pressure (Pa)	390	440	490	510
Motor Power (W)	130	150	178	224
Air outlet (ø inches)	6"	6"	6"	6"


Speed

Noise level perception on a standard ventilation hood



NRS®

Speed





ZEUS PRO NRS®

›Scotch brite stainless steel ›NRS® technology for a quieter kitchen ›Touch control + 24h function
›Led lighting ›Baffle filters
›Optional charcoal filter.

Wall
30" (76 cm)
36" (90 cm)

Motor and Control
600 CFM
4 speed touch control

Filters
Charcoal: optional


Lighting
Led

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FNZEU30W6SS
Wall 30" - (76 cm)
600 CFM

FNZEU36W6SS
36" - (90 cm)
600 CFM

Noise level 3rd speed:
45 dB(A)re1pW



If your ceiling height is 8' or less, a low profile elbow (KACL.605) **must** be installed.
See page 78.



PYRAMID PRO NRS®

›Scotch brite stainless steel ›NRS® technology for a quieter kitchen
›Touch control + 24h function ›Led lighting
›Baffle or labyrinth filters
›Optional charcoal filter.

Wall
30" (76 cm)
36" (90 cm)

Motor and Control
600 CFM
4 speed touch control

Filters
Charcoal: optional



Lighting
Led
30" (76 cm)
2x1,2 W (3200 K)
36" (90 cm) / 48" (120 cm)
3x1,2 W (3200 K)

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FNPYR30W6SS
Wall - 30" (76 cm)
600 CFM

FNPYR36W6SS
Wall - 36" (90 cm)
600 CFM

Noise level 3rd speed:
45 dB(A)re1pW



*If your ceiling height is 8' or less,
a low profile elbow (KACL.605)
must be installed.
See page 78.*



LINE PRO NRS®

›Scotch brite stainless steel (AISI 304) ›NRS® technology for a quieter kitchen ›Touch control + 24h function ›Led lighting ›Baffle filter ›Optional charcoal filter.


Noise level 3rd speed:
45 dB(A)re1pW

Wall
30" (76 cm)
36" (90 cm)

Motor and Control
600 CFM
4 speed touch control
Filters
High Performance Filter
Lighting
Led 3x1,2 W (3200 K)
**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FNLIN30W6SS
Wall – 30" (76 cm)
600 CFM

FNLIN36W6SS
Wall – 36" (90 cm)
600 CFM



If your ceiling height is 8' or less, a low profile elbow (KACL605) **must** be installed.
See page 78.



MASSIMO PRO NRS®

›Scotch brite stainless steel (AISI 304) ›NRS® technology for a quieter kitchen ›Touch control + 24h function ›LED lighting ›Baffle filters ›Optional charcoal filter ›Optional remote control.

105080053

Optional remote control



Built-in
30" (76 cm)
36" (90 cm)



Motor and Control
600 CFM
4 speed touch control
Filters
High performance filter

Lighting
22 1/16" (60 cm)
Led 2x1,2W (3200 K)
36" (90 cm)
LED 4x1.2 W (3200 K)
Minimum distance from cook top surface
22 7/16" (57 cm)

FNMAS30W6SS
Built-in – 30" (76 cm)
600 CFM

FNMAS36W6SS
Built-in – 36" (90 cm)
600 CFM

Noise level 3rd speed:
45 dB(A)re1pW



Cut-out size
30" (76 cm)
20 3/16" (512) x 9 13/16" (250)
36" (90 cm)
32 3/8" (822) x 9 13/16" (250)



LUMINA NRS®

›Scotch brite stainless steel (AISI 304) ›Tempered glass with steel finishing ›NRS® technology for a quieter kitchen ›Touch control + 24h function ›White neon ambient light ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Noise level 3rd speed:
45 dB(A)re1pW

Wall
36" (90 cm)

Motor and Control

500 CFM
4 speed touch control

Filters

High Performance Filter

Lighting

Neon 1x21 W

**Minimum distance
from cook top surface**
25 9/16" (65 cm)

FNLUM36W5SS
Wall – 36" (90 cm)
Steel – 500 CFM

Island
36" (90 cm)

Motor and Control

500 CFM
4 speed touch control

Filters


High Performance Filter

Lighting

Neon 2x21 W

**Minimum distance
from cook top surface**
25 9/16" (65 cm)

FNLUM36I5SS
Island – 36" (90 cm)
Steel – 500 CFM



If your ceiling height is 8' or less,
a low profile elbow (KACL.605)
must be installed.
See page 78.





PLANE NRS®

›Scotch brite stainless steel (AISI 304) ›NRS® technology for a quieter kitchen
›Electronic control ›Led lighting ›Air Falmec filter for balanced suction ›Optional charcoal filter.

*Available optional accessories:
Wall/island chimney extension - Silent/
conveyor NRS®.*

**Noise level 3rd speed:
45 dB(A)re1pW**

Wall
30" (76 cm)
36" (90 cm)

Motor and Control
500 CFM
4 speed electronic control

Filters
High Performance Filter

Lighting
Led
90 cm: 2x1,2 W (3200 K)
120 cm: 3x1,2 W (3200 K)

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FNPLS30W5SS
Wall - 30" (76 cm)
500 CFM

FNPLS36W5SS
Wall - 36" (90 cm)
500 CFM

Island
36" (90 cm)



Motor and Control
500 CFM
4 speed electronic control

Filters
High Performance Filter

Lighting
Led 4x1,2 W (3200 K)

**Minimum distance
from cook top surface**
63 cm

FNPLS36I5SS
Island - 36" (90 cm)
500 CFM



*If your ceiling height is 8' or less,
a low profile elbow (KACL.605)
must be installed.
See page 78.*



GRUPPO INCASSO NRS®

›Scotch brite stainless steel (AISI 304) ›NRS® technology for a quieter kitchen ›Electronic control ›Led lighting ›Top filter removable and washable ›Optional charcoal filter ›Remote control included.

Remote control included



Built-in
20" (50 cm)
28" (70 cm)

Motor and Control
500 CFM
4 speed electronic control


Filters
High performance filter

Lighting
Led 2x1,2W (3200 K)
Minimum distance from cook top surface
22 7/16" (57 cm)

FNINS20B5SS
Built-in - 20" (50 cm)
500 CFM

FNINS28B5SS
Built-in - 28" (70 cm)
500 CFM

Noise level 3rd speed:
45 dB(A)re1pW



Cut-out size
20" (50 cm)
19 15/16" (506) x 10 5/16" (262)
28" (70 cm)
29 9/16" (751) x 10 5/16" (262)



PROFESSIONAL

The hood for haute cuisine.

Our Professional hoods create an atmosphere of professionalism in the kitchen. More powerful motors, high-performance special filters, and unique filters designed to collect grease and oils. A blend of features that is typical of ventilation hoods found in the best restaurants but made especially for you and your home environment.



ZEUS PRO

- ›Scotch brite stainless steel
- ›Slider control ›Led lighting
- ›Baffle filters ›Optional charcoal filter.

Wall
30" (76 cm) 600 CFM
36" (90 cm) 600 CFM

Motor and Control
 600 CFM

Filters
 Charcoal: optional

Lighting
 Led

2x1,2 W (3200 K)
Minimum distance
from cook top surface
 24 13/16" (63 cm)

FP18P30W6SS
Professional 18
30" (76 cm)
 600 CFM

FP18P36W6SS
Professional 18
36" (90 cm)
 600 CFM

Wall
36" (90 cm) 2x500 CFM
48" (120 cm) 2x500 CFM

Motor and Control
 2x500 CFM

3+3 speed Slider

Filters
 Charcoal: optional


Lighting
 Led

3x1,2 W (3200 K)
Minimum distance
from cook top surface
 24 13/16" (63 cm)


FP18P36W9SS
Professional 18
36" (90 cm)
 2x500 CFM

FP18P48W9SS
Professional 18
48" (120 cm)
 2x500 CFM

30" (76 cm) 600 CFM
 36" (90 cm) 600 CFM



36" (90 cm) 2x500 CFM
 48" (120 cm) 2x500 CFM





PYRAMID PRO

- ›Scotch brite stainless steel
- ›Slider control ›Led lighting
- ›Baffle or labyrinth filters
- ›Optional charcoal filter.

Wall

30" (76 cm)
36" (90 cm)
48" (120 cm)

Motor and Control

30" (76 cm)
600 CFM - 3 speed Slider
36" (90 cm) / 48" (120 cm)
2x500 CFM - 3+3 speed Slider

Filters

Charcoal: optional

Lighting

Led
30" (76 cm)
2x1,2 W (3200 K)
36" (90 cm) / 48" (120 cm)
3x1,2 W (3200 K)

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FPDPR30W6SS

Wall - 30" (76 cm)
600 cfm

FPDPR36W9SS

Wall - 36" (90 cm)
2x500 CFM

FPDPR48W9SS

Wall - 48" (120 cm)
2x500 CFM

Island

36" (90 cm)

Motor and Control

2x500 CFM
3+3 speed Slider

Filters

Charcoal: optional




Lighting

4x1,2 W (3200 K)

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FPDPR36I9SS

Island - 36" (90 cm)
2x500 CFM





MASSIMO PRO

›Scotch brite stainless steel
›Slider control ›Led lighting
›Baffle filters ›Optional charcoal filter.

Built-in
34" (87 cm)
34 22" dept (87 cm – 22"dept)

Motor and Control
600 CFM
3 speed Slider control

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)

**Minimum distance
from cook top surface**
60 cm

FIMAS34B6SS-1

Built-in
34" (87 cm)
600 CFM

FIMAX34B9SS-1

Built-in
34" 22" dept (87 cm – 22"dept)
2x500 CFM

Built-in
34" (87 cm)
34" 22" dept (87 cm – 22"dept)
46" (116 cm)
46" 22" dept (116 cm – 22"dept)

Motor and Control
2x500 CFM
3+3 speed Slider control

Filters

Charcoal: optional

Lighting

Led 4x1,2 W (3200 K)

**Minimum distance
from cook top surface**
60 cm

FIMAS34B9SS-2

Built-in
34" (87 cm)
2x500 CFM

FIMAX34B9SS-1





Built-in
34" 22" dept
(87 cm – 22" dept)
2x500 CFM

FIMAS46B9SS-2


Built-in
46" (116 cm)
2x500 CFM

FIMAX46B9SS-1

Built-in
46" 22" dept
(116 cm – 22" dept)
2x500 CFM



Transition required to go from 2x6" round duct to 1x8" round duct is included with all dual motor units in this series





DESIGN

In search of the perfect ventilation hood.

A special collection of select models characterized by unique design and functional solutions. Design+ is Falmec's exclusive collection created in partnership with both established and emerging designers. An ongoing, shared "work in progress" that has allowed us to create a range that aims for absolute perfection: in design, materials and technological solutions.



PRISMA

›Tempered white or black glass ›Frontal frame in scotch brite stainless steel (AISI 304) ›Touch control ›Led lighting ›Led ambient light ›Top filters removable and washable ›Optional charcoal filter ›Possible to duct wall mounted from rear ›Optional wall chimney.

Wall
34" (85 cm)

Motor and Control
500 CFM
4 speed touch control

Filters
Charcoal: 6

Lighting
Led 2x1,2 W (3200 K)
Ambient led
2x1,2 W (3200 K)


**Minimum distance
from cook top surface**
20 7/8" (53 cm)

FDPRI36W5SW
Wall - 34" (85 cm)
White - 500 CFM


FDPRI36W5SB
Wall - 34" (85 cm)
Black - 500 CFM

KCQAN.00#I
Optional chimney
(Stainless steel)


Designed by Saggia-Sommella



Rear view



Optional chimney







POLAR

›Scotch brite stainless steel (AISI 304) ›Electronic control ›Led lighting
›Top filter removable and washable ›Optional charcoal filter.

Wall – 15" (35 cm)
Island – 15" (35 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 6

Lighting

Led 3x1,2 W (3200 K)

**Minimum distance
from cook top surface**





23 5/8" (60 cm)

FDPLR15W5SS
Wall – 15" (35 cm)
500 CFM

FDPGL36W0TG
Optional glass wall

FDPLR15I5SS
Island – 15" (35 cm)
500 CFM

FDPGL36I0TG
Optional glass island





PRESTIGE

›Scotch brite stainless steel (AISI 304) ›Curved tempered glass, black or white version
›Electronic control ›Led lighting ›Led ambient light
›Top filter removable and washable ›Optional charcoal filter ›Possible to duct wall mounted from rear.

ISLAND. Without extension: chimney H 786 mm / with extension: chimney H min. 1100 mm - max 1360 mm.

Wall – 26" (65 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 6

Lighting

Led 4x1,2 W (4200 K)
Led stripe 7 W (4200 K)

**Minimum distance
from cook top surface**
23 5/8" (60 cm)

FDPST26W5SGW

Wall – 26" (65 cm)
White – 500 CFM

FDPST26W5SG

Wall – 26" (65 cm)
Black – 500 CFM

Island – 30" (75 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 6

Lighting

Led 4x1,2 W (4200 K)
Led stripe 13 W (4200 K)

**Minimum distance
from cook top surface**
23 5/8" (60 cm)



FDPST30I5SGW

Island – 30" (75 cm)
White – 500 CFM

FDPST30I5SG

Island – 30" (75 cm)
Black – 500 CFM

Emo Design





NUVOLA 90

›Scotch brite stainless steel (AISI 304) ›Tempered extra light painted glass ›Perimeter suction ›Electronic control ›Neon lighting ›Metallic grease filter, removable and washable ›Remote control included.

Remote control included



Motor sold separately

Ceiling – 36" (90 cm)

Motor and Control

600 CFM
4 speed electronic control

Lighting

Neon 2x39 W

Maximum distance from cook top surface

59 1/16" (150 cm)

FDNUV36C6SS

Ceiling – Steel
36" (90 cm)


KACL.798#41F

Motor 600 CFM

KACL.789


Junction

View with under-roof/remote motor mounted



Cut-out size
19 7/8" (505) x 37" (940)

Side view with junction





NUVOLA 140

›Scotch brite stainless steel (AISI 304) ›Tempered extra light painted glass
›Perimeter suction
›Electronic control ›Neon lighting ›Metallic grease filter, removable and washable ›Remote control included.

Remote control included



Motor sold separately

Ceiling - 54" (140 cm)

Motor and Control

600 CFM
4 speed electronic control

Lighting

Neon 2x58 W

Maximum distance from cook top surface

59 1/16" (150 cm)

FDNUV54C6SS

Ceiling - Steel
54" (140 cm)


KACL.798#41F

Motor 600 CFM

KACL.789

Junction


View with under-roof/remote motor mounted



Cut-out size

23 1/4" (590) x 52 3/16" (1325)

Side view with junction



Beautiful innovations for your kitchen



NUBE

- ›Scotch brite stainless steel (AISI 304) ›Perimeter suction ›Electronic control
- ›Metallic grease filter, removable and washable
- ›Remote control included.

Remote control included



Motor sold separately

Ceiling – 36" (90 cm)

Motor and Control


600 CFM
4 speed electronic control
Maximum distance from cook top surface
59 1/16" (150 cm)

FDNUB36C6SS
Ceiling 36" (90 cm)
Steel – 600 CFM

KACL.798#41F
Motor 600 CFM


KACL.789
Junction

View with under-roof/remote motor mounted



Cut-out size
19 7/8" (505) x 37" (940)

Side view with junction





STELLA

- ›Scotch brite stainless steel (AISI 304 ›Perimeter suction ›Electronic control
- ›Dimmable led lighting
- ›Metallic grease filter, removable and washable
- ›Remote control included.

Remote control included



Motor sold separately

Ceiling
36" (90 cm)
48" (120 cm)

Motor and Control
600 CFM
4 speed electronic control

Lighting
Led 4x3,6 W (4000 K)
Maximum distance from cook top surface
59 1/16" (150 cm)


FDSTE36C6SS
Ceiling 36" (90 cm)
Steel – 600 CFM

FDSTE48C6SS
Ceiling 48" (120 cm)
Steel – 600 CFM

KACL.798#41F
Motor 600 CFM


KACL.789
Junction

View with under-roof/remote motor mounted



Cut-out size
36" (90 cm)
19 7/8" (505) x 37" (940) 120
48" (120 cm)
19 7/8" (505) x 48 13/16" (1240)

Side view with junction





QUASAR

›Scotch brite stainless steel
›Finishing tempered glass:
white or black ›Perimeter
suction ›Touch control +
24h function ›Led lighting
›Metallic grease filter,
removable and washable
›Optional charcoal filter
›Possible to duct wall
mounted from rear ›Optional
wall chimney.



RAL 9016
White



RAL 9005
Black

*The RAL codes have to be considered indicative
since production process and materials may alter
the colors.*

Wall
36" (90 cm)

Motor and Control

500 CFM
4 speed touch control

Filters

Charcoal: 6

Lighting

Led
3x1,2 W (3200 K)

Minimum distance
from cook top surface
20 1/2" (52 cm)

FDQWH36W5SG


Wall - 36" (90 cm)
White - 500 CFM

FDQBK36W5SG


Wall - 36" (90 cm)
Black - 500 CFM

KCQAN.00#I


Optional chimney
(Stainless steel)



Rear view



Optional chimney





FLIPPER

›Glass versions with Fasteel central band ›Electronic control ›Led lighting
›Metallic grease filter, removable and washable
›Optional charcoal filter
›Optional wall chimney.

 **RAL 9016**
Satin white

 **RAL 9005**
Satin black

The RAL codes have to be considered indicative since production process and materials may alter the colors.

Wall – 34" (85 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 6

Lighting

Led 2x1,2 W (3200 K)

Minimum distance from cook top surface

20 1/2" (52 cm)

FDFLI36W5SW

Wall – 34" (85 cm)

Satin white – 500 CFM


FDFLI36W5SB

Wall – 34" (85 cm)


Satin black – 500 CFM

KCQAN.00#I


Optional chimney
(Stainless steel)



Rear view



Optional chimney









LUMEN

›Scotch brite stainless steel (AISI 304) ›Electronic control ›Neon lighting ›Neon ambient light ›Air Falmec filter for balanced suction ›Optional charcoal filter.

Wall
24" (60 cm)
36" (90 cm)

Motor and Control

280 CFM
3 speed electronic control
500 CFM
4 speed electronic control

Filters

Charcoal: 3

Lighting

24" (60 cm)
Neon 1x13 W
36" (90 cm)
Neon 1x21 W

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

Island
36" (90 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 3

Lighting



Neon 2x21 W

**Minimum distance
from cook top surface**
24 13/16" (63 cm)

FDLUM24W3SS
Wall – 24" (60 cm)
280 CFM

FDLUM36W5SS
Wall – 36" (90 cm)
500 CFM

FDLUM36I5SS
Island – 36" (90 cm)
500 CFM



LUMEN ISOLA 175

›Scotch brite stainless steel (AISI 304) ›Perimeter suction ›Double electronic control on both sides ›Neon ambient light on both sides ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Island – 70" (175 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 3

Lighting

Led 12x1,2 W (3200 K)


Minimum distance

from cook top surface
24 13/16" (63 cm)

FDLUM70I5SS-1

Island – 70" (175 cm)

500 CFM







MOVE

›Scotch brite stainless steel (AISI 304) ›Black or white tempered glass ›Sliding door ›Electronic control ›Led lighting ›Metallic grease filter, removable and washable ›Optional combined regeneratable Carbon.Zeo filter ›Optional chimney ›Optional glass shelf ›Possible to duct wall mounted from rear.

Built-in
24" (60 cm)
36" (90 cm)

Motor and Control
500 CFM
4 speed electronic control

Filters
Charcoal.Zeolite optional
Lighting
Led

24" (60 cm)
2x1,2 W (3200 K)
36" (90 cm)
3x1,2 W (3200 K)

Minimum distance from cook top surface
20 1/2" (52 cm)

FDMOV24W5SW
Built-in – 24" (60 cm)
White – 500 CFM

FDMOV24W5SB
Built-in – 24" (60 cm)
Black – 500 CFM

FDMOV36W5SW
Built-in – 36" (90 cm)
White – 500 CFM

FDMOV36W5SB
Built-in – 36" (90 cm)
Black – 500 CFM


KACL.934
Charcoal.Zeolite filter

KACL.106
Optional glass shelf
24" (60 cm)


KACL.107
Optional glass shelf
36" (90 cm)

KCVJN.00#3
Optional telescopic chimney
h 72 13/16" (185 cm)
+ h 72 13/16" (185 cm)


KCVJN.01#3
Optional chimney
h 47 1/4" (120 cm)




Rear view



Optional chimney




Optional shelf



Control

Indication of controls on the frontal panel (The control is in the upper side).





VIRGOLA

›Scotch brite stainless steel ›Tempered turning glass ›Electronic control ›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Built-in
24" (60 cm)
36" (90 cm)

Motor and Control
280 CFM
3 speed electronic control



Filters
Charcoal: 3

Lighting
Led 2x1,2 W (3200 K)

**Minimum distance
from cook top surface**
20 1/2" (52 cm)

FDVRG24W3SS
Built-in – 24" (60 cm)
280 CFM

FDVRG36W3SS
Built-in – 36" (90 cm)
280 CFM







DOWN DRAFT

›Scotch brite stainless steel (AISI 304) ›Tempered white or black glass or steel panel
›Perimeter suction ›Touch control + 24 h ›Led lighting
›Top filter removable and washable ›Optional remote control.

*Available optional accessories:
Remote motors.*

**36" (90 cm)
48" (120 cm)**

Motor and Control

600 CFM
4 speed touch control

Lighting

Led Strip 10 W (5500 K)

Minimum distance from cooker top

2 3/8" (60 mm)

FDDOW36T6SGW

Down Draft – 36" (90 cm)

White

FDDOW36T6SGB

Down Draft – 36" (90 cm)

Black

FDDOW36T6SS

Down Draft – 36" (90 cm)

Steel

FDDOW48T6SGW

Down Draft – 48" (120 cm)

White

FDDOW48T6SGB

Down Draft – 48" (120 cm)

Black

FDDOW48T6SS

Down Draft – 48" (120 cm)

Steel

KACL.930

Kit Carbon.Zeo filters


105080053

Optional remote control



Cut-out size

36" (90 cm): 3" 7/8 x 31" 7/8
48" (120 cm): 3" 7/8 x 43" 11/16







FASTEEL

Absolutely no fingerprints.

With Fasteel fingerprint-proof steel, the hood stays beautiful and shiny thanks to the innovative “No Finger-Print technology”. This is a special finish that prevents the appearance of halos and fingerprints on the surface, thus making cleaning a breeze.



LUX

›Scotch brite Fasteel no finger prints ›Etched tempered extra light glass ›Perimeter suction ›Electronic control ›Neon lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

WALL. Without extension: chimney H 22" (560 mm) / with extension: chimney H min. 35 5/16" (770 mm) - max 41 3/4" (1060 mm). ISLAND. Without extension: chimney H 25 3/16" (640 mm) / with extension: chimney H min. 33 7/16" (850 mm) - max 47 5/8" (1210 mm).

Wall
36" (90 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 3

Lighting

Neon 2x21 W

Minimum distance

from cook top surface
25 9/16" (65 cm)

FFLUX36W5SS

Wall – 36" (90 cm)

Fasteel – 500 CFM

Island
36" (90 cm)

Motor and Control

500 CFM
4 speed elettronic control

Filters

Charcoal: 3

Lighting

Neon 2x28 W



Minimum distance

from cook top surface
25 9/16" (65 cm)

FFLUX36I5SS

Island – 36" (90 cm)

Fasteel – 500 CFM





PLANE TOP

›Scotch brite Fasteel no finger prints ›Perimeter suction ›Electronic control ›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Wall
36" (90 cm)
48" (120 cm)

Motor and Control
500 CFM
4 speed electronic control

Filters
Charcoal: 3

Lighting
Led
36" (90 cm)
2x1,2 W (3200 K)
48" (120 cm)
3x1,2 W (3200 K)

Minimum distance from cook top surface
24 13/16" (63 cm)

FFPLN36W5FS
Wall – 36" (90 cm)
Fasteel – 500 CFM

FFPLN48W5FS
Wall – 48" (120 cm)
Fasteel – 500 CFM



Island
36" (90 cm)

Motor and Control
500 CFM
4 speed electronic control

Filters
Charcoal: 3

Lighting
Led 4x1,2 W (3200 K)
Minimum distance from cook top surface
24 13/16" (63 cm)

FFPLN36I5FS
Island – 36" (90 cm)
Fasteel – 500 CFM





MIRA TOP

›Scotch brite Fasteel no finger prints ›Perimeter suction ›Electronic control ›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

**Adjustable gap.

ISLAND. Without extension: chimney H 29 1/2" (750 mm) / with extension: chimney H min. 35 7/16" (900 mm) - max 47 5/16" (1202 mm).

Wall
16" (40 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 3

Lighting

Led 2x1,2 W (3200 K)

Minimum distance

from cook top surface
23 5/8" (60 cm)

FFMIR16W5FS

Wall telescopic

16" (40 cm)

Fasteel - 500 CFM

Island
16" (40 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 6

Lighting

Led 4x1,2 W (3200 K)

Energy class

B

Minimum distance



from cook top surface
23 5/8" (60 cm)

FFMIR16I5FS


Island

16" (40 cm)

Fasteel - 500 CFM







RIALTO TOP

›Scotch brite Fasteel no finger prints and black satin finishing sides ›Electronic control ›Led lighting ›Led ambient light ›Top filter removable and washable ›Optional charcoal filter.

Wall – 24" (55 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: 6

Lighting

Led 2x1,2 W (3200 K)
Led stripes
2x2 W (5500 K)

**Minimum distance
from cook top surface**


19 11/16" (50 cm)

FFRIA24W5FS

Wall – 24" (55 cm)

Fasteel – 500 CFM

Design Antoniazzi&Niolu



reddot design award
winner 2010



POTENZA

A collection that offers great value and performance.
Falmec Potenza Series features two distinct power levels in most models to suit your individual needs. These models embody the classic characteristics of Italian design.



MERCURIO

›Scotch brite stainless steel ›Electronic control
›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Mercurio Wall

24" (60 cm)

30" (76 cm)

36" (90 cm)

Motor and Control

280 CFM

3 speed Electronic control

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)

Minimum distance from cook top surface

24 13/16" (63 cm)

FPMER24W3SS

Mercurio Wall

24" (60 cm)

280 CFM

FPMER30W3SS

Mercurio Wall

30" (76 cm)

280 CFM

FPMER36W3SS

Mercurio Wall

36" (90 cm)

280 CFM

MercurioXL Wall

30" (76 cm)

36" (90 cm)

MercurioXL Island

36" (90 cm)

42" (106 cm)

Motor and Control

600 CFM

4 speed Electronic control

Filters

Charcoal: optional

Lighting

Wall: Led 2x1,2 W (3200 K)

Island: Led 4x1,2 W (3200 K)

Minimum distance from cook top surface

24 13/16" (63 cm)

FPMEX30W6SS

MercurioXL Wall

30" (76 cm)

600 CFM

FPMEX36W6SS

MercurioXL Wall

36" (90 cm)

600 CFM

FPMEX36I6SS

MercurioXL Island

36" (90 cm)

600 CFM


FPMEX42I6SS

MercurioXL Island


42" (106 cm)

600 CFM


Mercurio Wall



Mercurio XL Wall



Mercurio XL Island





VULCANO

›Scotch brite stainless steel
›Electronic or mechanical control
›Led lighting
›Metallic grease filter, removable and washable or Labyrinth filters
›Optional charcoal filter.

Vulcano Wall

24" (60 cm)
30" (76 cm)
36" (90cm)

Motor and Control

24" (60 cm)
280 CFM
3 speed Mechanical control
30" (76 cm) / 36" (90 cm)
280 CFM
3 speed Electronic control

Filters

Charcoal: optional

Lighting

24" (60 cm)
No light
30" (76 cm) / 36" (90 cm)
Led 2x1,2 W (3200 K)

Minimum distance from cook top surface

23 5/8" (60 cm)

FPVUL24W3SS

Vulcano Wall
24" (60 cm)
280 CFM

FPVUL30W3SS

Vulcano Wall
30" (76 cm)
280 CFM

FPVUL36W3SS

Vulcano Wall
36" (90cm)
280 CFM

VulcanoXL Wall

30" (76 cm)
36" (90cm)

Motor and Control

600 CFM
4 speed Electronic control

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)

Minimum distance from cook top surface

23 5/8" (60 cm)


FPVUX30W6SS

VulcanoXL Wall
30" (76 cm)
600 CFM


FPVUX36W6SS

VulcanoXL Wall
36" (90cm)
600 CFM

Vulcano Wall



Vulcano XL Wall





ARTEMIDE

›Scotch brite stainless steel ›Electronic control
›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

ArtemideXL Wall

30" (76 cm)

36" (90 cm)

Motor and Control

600 CFM

4 speed Electronic control

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)

Minimum distance from cook top surface

23 5/8" (60 cm)

FPARX30W6SG

ArtemideXL Wall

30" (76 cm)



600 CFM

FPARX36W6SG

ArtemideXL Wall

36" (90 cm)

600 CFM





AFRODITE

- ›Scotch brite stainless steel
- ›Slider control ›Led lighting
- ›Metallic grease filter, removable and washable
- ›Optional charcoal filter.

AfroditeXL Wall
30" (76 cm)
36" (90 cm)

Motor and Control
 600 CFM
 3 speed Slider control


Filters
 Charcoal: optional

Lighting
 Led 2x1,2 W (3200 K)

**Minimum distance
 from cook top surface**
 23 5/8" (60 cm)

FPAFX30W6SS
AfroditeXL Wall
30" (76 cm)
 600 CFM

FPAFX36W6SS
AfroditeXL Wall
36" (90 cm)
 600 CFM





SABINA

›Scotch brite stainless steel
›Slider control ›Led lighting
›Metallic filter, removable
and washable ›Optional
charcoal filter.

Built-in
22" (56 cm)
28" (72 cm)

Motor and Control

280 CFM
3 speed slider

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)


Minimum distance
from cook top surface
24 7/16" (62 cm)

FISAB22B3SS

Built-in – 22" (56 cm)
280 CFM

FISAB28B3SS

Built-in – 28" (72 cm)
280 CFM



Cut-out size
10 5/17" (262) x 19 5/8" (498)



VALENTINA

›Scotch brite stainless steel ›Electronic control
›Led lighting ›Metallic grease filter, removable and washable ›Perimeter suction
›Optional charcoal filter.

Built-in
28" (72 cm)
34" (87 cm)

Motor and Control

500 CFM
4 speed electronic control

Filters

Charcoal: optional

Lighting

28" (72 cm)

Led 2x1,2 W (3200 K)

34" (87 cm)

Led 4x1,2 W (3200 K)


Minimum distance
from cook top surface
24 7/16" (62 cm)

FIVAL28B5SS-1

Built-in – 28" (72 cm)
500 CFM

FIVAL34B5SS-1

Built-in – 34" (87 cm)
500 CFM



Cut-out size

28" (72 cm)

10 5/16" (262) x 26 1/4" (666)

34" (87 cm)

10 5/16" (262) x 31 15/16" (812)



BUILT-IN MERCURIO

›Scotch brite stainless steel ›Electronic control
›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Built-in
30" (76 cm)
36" (90 cm)

Motor and Control
280 CFM
3 speed Electronic control


Filters
Charcoal: optional

Lighting
Led 2x1,2 W (3200 K)

**Minimum distance
from cook top surface**
23 5/8" (60 cm)

FPMEU30B3SS
Built-in – 30" (76 cm)
280 CFM

FPMEU36B3SS
Built-in – 36" (90 cm)
280 CFM





MARA

›Scotch brite stainless steel ›Slider control
›Led lighting ›Metallic grease filter, removable and washable ›Optional charcoal filter.

Built-in
22" (56 cm)
28" (72 cm)

Motor and Control
600 CFM
3 speed Slider control


Filters
Charcoal: optional

Lighting
Led 2x1,2 W (3200 K)

**Minimum distance
from cook top surface**
23 5/8" (60 cm)

FIMAR22B6SS
Built-in – 22" (56 cm)
600 CFM

FIMAR28B6SS
Built-in – 28" (72 cm)
600 CFM



Cut-out size
22" (56 cm)
10 5/16" (262) x 19 5/8" (498)
28" (72 cm)
10 5/16" (262) x 26 1/4" (666)



DANILO

›Scotch brite stainless steel
›Slider control ›Led lighting
›Labyrinth filters ›Optional
charcoal filter.

Built-in
28" (72 cm)

Motor and Control

600 CFM
3 speed Slider control

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)

Minimum distance
from cook top surface

23 5/8" (60 cm)

FIDAN28B6SS-1

Built-in – 28" (72 cm)

600 CFM

Built-in
28" (72 cm)

Motor and Control

2x500 CFM
3+3 speed Slider control

Filters

Charcoal: optional

Lighting

Led 2x1,2 W (3200 K)

Minimum distance
from cook top surface


23 5/8" (60 cm)

FIDAN28B9SS-2


Built-in – 28" (72 cm)

2x500 CFM


Danilo 28" (72 cm) - 600 CFM



Danilo 28" (72 cm) - 2x500 CFM



Transition required to go from 2x6" round
duct to 1x8" round duct is included with all
dual motor units in this series





EROS

- ›Scotch brite stainless steel
- ›Electronic control ›Led lighting ›Labyrinth filters
- ›Optional charcoal filter.

Built-in
28" (72 cm)


Motor and Control
500 CFM
4 speed Electronic control

Filters
Charcoal: optional

Lighting
Led 2x1,2 W (3200 K)

Minimum distance
from cook top surface
23 5/8" (60 cm)


FPERO30U5SS
Built-in – 28" (72 cm)
500 CFM





ACCESSORIES


Ducting accessories



Rigid round ducting
KACL.382 $\varnothing 4\ 15/16'' \times 47\ 1/4''$ ($\varnothing 125 \times 1200$)
KACL.358 $\varnothing 5\ 15/16'' \times 47\ 1/4''$ ($\varnothing 150 \times 1200$)
KACL.340 $\varnothing 7\ 7/8'' \times 47\ 1/4''$ ($\varnothing 200 \times 1200$)




Junction
KACL.343 $\varnothing 5\ 15/16''$ (150) / $\varnothing 7\ 7/8''$ (200)



Round aluminium ducting extensible to 118".
KACL.359 $\varnothing 4\ 15/16'' \times 32''$ -118" ($\varnothing 125\text{ mm} \times 800$ -3000 mm)
KACL.360 $\varnothing 5\ 15/16'' \times 32''$ -118" ($\varnothing 150\text{ mm} \times 800$ -3000 mm)



Round junction
KACL.384 $\varnothing 4\ 15/16''$ (125 mm)
KACL.380 $\varnothing 5\ 15/16''$ (150 mm)
KACL.342 $\varnothing 7\ 7/8''$ (200 mm)




Bracket for round ducting
KACL.392 $\varnothing 4\ 15/16''$ (125) / $\varnothing 5\ 15/16''$ (150)




Clamp for flexible ducting
KACL.363 $\varnothing 4\ 15/16''$ (125 mm)
KACL.364 $\varnothing 5\ 15/16''$ (150 mm)



Round elbow
KACL.390 $\varnothing 4\ 15/16''$ (125 mm)
KACL.391 $\varnothing 5\ 15/16''$ (150 mm)
KACL.341 $\varnothing 7\ 7/8''$ (200 mm)



Flange
KACL.396 $\varnothing 7\ 7/8''$ (200 mm)



Gravity wings grid
KACL.347 $\varnothing 4\ 15/16''$ (125 mm)
KACL.348 $\varnothing 5\ 15/16''$ (150 mm)

Remote control



Remote Control
105080053

Magic Steel



Protective cleaning cloths for stainless steel surfaces.

KACL.815 (box 10 pcs)

Air flow conveyer for re-circulation verions

These accessories have been studied to improve the air flow in the re-circulation version of ventilating hoods. They will be available in three different version, depending on the dimension of the chimneys. The Kit includes a 11 3/16" (300 mm), 5 15/16" (150 mm) diameter piping to drive the air to the conveyer. AVAILABLE ONLY FOR 500 CFM MOTORS.



Island

Lumen - Lumen 175 - Lux - Mira Top -
Plane - Plane Top

KACL.866



Wall

Lumen - Plane - Plane Top




KACL.864



Wall

Flipper - Mira Top

KACL.865



Filters

The filters are designed to optimize performance and collecting cooking greases. They can be washed in a dishwasher.



Base

9 1/4"x9 5/8" (235x245 mm)
cod. 101079900

9 1/4"x9 5/8" (235x245 mm)
cod. 101079950*

9 1/4"x9 5/8" (235x245 mm)
cod. 101079951**

10 13/16"x10 13/16" (274x274 mm)
cod. 101080240

10 15/16"x 11 9/16" (277x294 mm)
cod. 101080244

9 5/8"x 7 1/2" (245x190 mm)
cod. 101080145

Quasar
11 7/16"x12 13/16" (290x326 mm)
cod. 101080241

Nuvola - Nube
11 7/16"x 10 1/2" (290x267 mm)
cod. 101080243

Virgola 24" (60 cm)
9 5/8"x 8 1/8" (245x207 mm)
cod. 101079909

Virgola 36" (90 cm)
8"x8 1/8" (204x207 mm)
cod. 101079910

* Painted white
** Painted black



Top

Plane NRS®
10 15/16"x 11 7/8" (278x301 mm)

cod. 101080126

Prestige
13 5/16"x8 1/2" (338x216 mm)
cod. 101080095

Polar
cod. KACL.841#1
Down Draft 36" (90 cm)
10"x8 1/2" (254x216 mm)

cod. 101080094
Down Draft 48" (120 cm)
15 15/16"x8 1/2" (404x216 mm)
cod. 101080093



AirFalmec

Lumen Wall 24"
Wall 10 15/16"x11 7/8" (278x301 mm)
cod. 101078700

Lumen Wall 36"
Wall 11 3/16"x11 7/8" (285x301 mm)
cod. 101078702

Lumen Island 36"
11 3/16"x11 7/8" (285x301 mm)
cod. 101078703

Balanced suction

Pressure and air velocity in the suction side of the hood are naturally higher in areas close to the motor. As a result, suction capacity is concentrated directly under the motor, leading to a general loss of performance, especially in the filter peripheral area. AirFalmec, the new balanced filter system, features a new design that can overcome this limitation by redistributing the aspiration for maximum efficiency and a greater capacity of the extractor, even in the furthest corners of the hood.

Filters



Baffle

13 3/4" x 15 3/4" (400x350 mm)

cod. 101080195

13 3/4" x 13 3/4" (350x350 mm)

cod. 101080196



Charcoal Filters

The anti-odour filters should only be installed in the ductless, re-circulating systems. The active carbon inside the filter absorbs cooking odours and smells. The carbon filters are consumed with use and we recommend replacing them every four months.

Square

Square charcoal filter - type 3

cod. 103050107

Round

Round charcoal filter ø8 3/8" (212 mm)

- type 2

cod. 103050102 (couple)

Round charcoal filter ø6 11/16" (170 mm)

- type 6

cod. 103050091 (couple)



High Performance Charcoal Filters



The High Performance Charcoal filters used in the NRS® range are composed of a active charcoal filtering membrane in and an external metal grid. This filter therefore has the dual function of both retaining the cooking grease and eliminating odors.

A fundamental characteristic of these filters is their long life; active charcoal filters can be cleaned and regenerated by first washing them in the dishwasher (at a temperature not higher than 65°C/150°F) and then drying them into the oven at a temperature of 100°C/212°F for 10 minutes. Considering a normal use of the hood, after three years, the filter should be replaced.

Lumina NRS®

2x 101078900

Gruppo Incasso NRS®

KACL.920

Plane NRS®

KACL.921

Extra lenght extensionH 28" (700 mm) Wall

Lux
KACL.490#X

Mercurio - Mercurio XL - Vulcano
KACL.510#I

Plane Top
KACL.510#X

Lumina NRS® - Plane NRS®
KACL.570#I

H 38" (960 mm) Wall

Lux
KACL.492#X

Mercurio - Mercurio XL - Vulcano
KACL.512#I

Plane Top
KACL.512#X

Lumina NRS® - Plane NRS®
KACL.571#I

H 48" (1200 mm) Island

Mercurio - Mercurio XL
KACL.557#I

Plane Top
KACL.557#X


Lumina NRS® - Plane NRS®
KACL.572#I

Lumen isola 175
KACL.557#I + KACL.350

MotorsRemote under-roof motor
600 CFM


Under-roof extractor fan 600 CFM.
Kit external motor 23 feet (7 m) wiring.
Suitable for hoods provided with
500 CFM motor only
(if used as remote under-roof unit).

KACL.798#21F

NRS® AccessoriesNRS® Silent/Conveyor


In order to improve the air flow in the
NRS® products, used in re-circulation
versions, it is available a new accessory.
This product gives to the customer the
possibility to reduce the noise level.

KACL.400

PVC Low profile elbow for tight
clearances

Reduces overall height requirements by
5 1/4 inches. Must be installed on wall-
mounted NRS® products to fit in rooms
where ceiling height is 8' or less.

KACL.605





Falmec S.p.A

via dell'Artigianato, 42 z.i.
31029 Vittorio Veneto
Treviso — Italy
info@falmec.com

www.falmecnorthamerica.com

Falmec declines all responsibility for any inaccuracies contained in this catalogue due to typos and copying errors. This catalogue supersedes and replaces all previous ones.

Falmec Spa hereby reserves the right to make - at any moment and without prior notice - all the technical, aesthetic and functional alterations to the products that it believes necessary for their improvement. Models, images and technical solutions presented in this catalogue are protected by industrial property rights.

The printing process does not always faithfully reproduce tones and materials of original.

This catalogue is of exclusive property of Falmec Spa. All rights are reserved. Any form of total or partial reproduction of catalogue is strictly forbidden.



credits

graphic design
Designwork

photo
Paolo Contratti
ContrattiCompany

stylist
Vanda Gemino

copy
Daniele Varelli